



ELECTRICAL CHARACTERISTICS: (PE-65499, COMPATIBLE)

1. D.C.R. : PRI. = 2.4 OHM+/-25% SEC. = 4.4 OHM+/-25%
2. INDUCTANCE (@10KHZ, 100mVrms) :
 - 1-4 (2-3 SHORT) = 22mH MIN.
 - 5-8 (6-7 SHORT) = 22mH MIN.
3. LEACKAGE INDUCTANCE (@100KHZ, 100mVrms) :
 - 13-16 (2-3, 1-4, 14-15 SHORT) = 11uH MAX.
 - 9-12 (6-7, 5-8, 10-11 SHORT) = 11uH MAX.
4. INTERWINDING CAP. (@100KHZ, 100mVrms) :
 - PRI. - SEC. = 100 pF MAX.
5. TURNS RATIO (@10KHZ, 100mVrms)
 - PRI : SEC = 1 : 2 +/-2%
6. HI-POT (2KVAC, 1mA, 2SEC) : PRI. - SEC.

					 Atech Technology Co., Ltd. <small>TEL:(02)2794-8667 FAX:(02)2794-8004</small>		TITLE ISDN-S TRANSFORMER	
							DWG. NO. ATPL-018A	
RELEASE	11/03/98	PAIR		SUEDY	UNITS: M/M	SAFETY		
NO. DESCRIPTION	DATE	BY	CHK	APPD	DATE			SHEET 1 OF 1
REVISIONS					11/03/98	DRAW <i>Pair</i>		